

## **LM137HV/LM237HV/LM337HV 3-Terminal Adjustable Negative Regulators (High Voltage)**

### **General Description**

The LM137HV/LM237HV/LM337HV are adjustable 3-terminal negative voltage regulators capable of supplying in excess of  $-1.5\text{A}$  over an output voltage range of  $-1.2\text{V}$  to  $-47\text{V}$ . These regulators are exceptionally easy to apply, requiring only 2 external resistors to set the output voltage and 1 output capacitor for frequency compensation. The circuit design has been optimized for excellent regulation and low thermal transients. Further, the LM137HV series features internal current limiting, thermal shutdown and safe-area compensation, making them virtually blowout-proof against overloads.


The LM137HV/LM237HV/LM337HV serve a wide variety of applications including local on-card regulation, programmable-output voltage regulation or precision current regulation. The LM137HV/LM237HV/LM337HV are ideal complements to the LM117HV/LM217HV/LM317HV adjustable positive regulators.

### **Features**

- Output voltage adjustable from  $-1.2\text{V}$  to  $-47\text{V}$
- $1.5\text{A}$  output current guaranteed,  $-55^{\circ}\text{C}$  to  $+150^{\circ}\text{C}$
- Line regulation typically  $0.01\%/\text{V}$
- Load regulation typically  $0.3\%$
- Excellent thermal regulation,  $0.002\%/\text{W}$
- $77\text{ dB}$  ripple rejection
- Excellent rejection of thermal transients
- $50\text{ ppm}/^{\circ}\text{C}$  temperature coefficient
- Temperature-independent current limit
- Internal thermal overload protection
- $100\%$  electrical burn-in
- Standard 3-lead transistor package

### **Typical Applications**

**Adjustable Negative Voltage Regulator**



$$-V_{OUT} = -1.25V \left( 1 + \frac{R2}{120\Omega} \right)$$

<sup>\*</sup>C2 =  $1\text{ }\mu\text{F}$  solid tantalum or  $10\text{ }\mu\text{F}$  aluminum electrolytic required for stability.  
Output capacitors in the range of  $1\text{ }\mu\text{F}$  to  $1000\text{ }\mu\text{F}$  of aluminum or tantalum electrolytic are commonly used to provide improved output impedance and rejection of transients.

<sup>\*</sup>C2 =  $1\text{ }\mu\text{F}$  solid tantalum is required only if regulator is more than 4" from power-supply filter capacitor

**Absolute Maximum Ratings**

Power Dissipation	Internally limited
Input-Output Voltage Differential	50V
Operating Junction Temperature Range	
LM137HV	-55°C to +150°C
LM237HV	-25°C to +150°C
LM337HV	0°C to +125°C
Storage Temperature	-65°C to +150°C
Lead Temperature (Soldering, 10 seconds)	300°C

**Preconditioning**

Burn-In in Thermal Limit                          100% All Devices

**Electrical Characteristics** (Note 1)


PARAMETER	CONDITIONS	LM137HV/LM237HV			LM337HV			UNITS
		MIN	TYP	MAX	MIN	TYP	MAX	
Line Regulation	$T_A = 25^\circ C, 3V \leq  V_{IN}-V_{OUT}  \leq 50V,$ (Note 2)		0.01	0.02		0.01	0.04	%/V
Load Regulation	$T_A = 25^\circ C, 10mA \leq I_{OUT} \leq I_{MAX}$ $ V_{OUT}  \leq 5V, (\text{Note 2})$ $ V_{OUT}  \geq 5V, (\text{Note 2})$		15	25	15	50	1.0	mV %
Thermal Regulation	$T_A = 25^\circ C, 10\text{ ms Pulse}$	0.002	0.02		0.003	0.04		%/W
Adjustment Pin Current		65	100		65	100		μA
Adjustment Pin Current Change	$10mA \leq I_L \leq I_{MAX}$ $2.5V \leq  V_{IN}-V_{OUT}  \leq 50V,$ $T_A = 25^\circ C$	2	5		2	5		μA
Reference Voltage	$T_A = 25^\circ C, (\text{Note 3})$ $3 \leq  V_{IN}-V_{OUT}  \leq 50V, (\text{Note 3})$ $10mA \leq I_{OUT} \leq I_{MAX}, P \leq P_{MAX}$	-1.225 -1.200	-1.250 -1.250	-1.275 -1.300	-1.213 -1.200	-1.250 -1.250	-1.287 -1.300	V V
Line Regulation	$3V \leq  V_{IN}-V_{OUT}  \leq 50V, (\text{Note 2})$	0.02	0.05		0.02	0.07		%/V
Load Regulation	$10mA \leq I_{OUT} \leq I_{MAX}, (\text{Note 2})$ $ V_{OUT}  \leq 5V$ $ V_{OUT}  \geq 5V$		20	50	20	70		mV %
Temperature Stability	$T_{MIN} \leq T_j \leq T_{MAX}$	0.6			0.6			%
Minimum Load Current	$ V_{IN}-V_{OUT}  \leq 50V$ $ V_{IN}-V_{OUT}  \leq 10V$	2.5 1.2	5 3		2.5 1.5	10 6		mA mA
Current Limit	$ V_{IN}-V_{OUT}  \leq 13V$ K Package H Package $ V_{IN}-V_{OUT}  = 50V$ K Package H Package	1.5 0.5 0.2 0.1	2.2 0.8 0.4 0.17	3.2 1.6 0.8 0.5	1.5 0.5 0.1 0.050	2.2 0.8 0.4 0.17	3.5 1.8 0.8 0.5	A A
RMS Output Noise, % of $V_{OUT}$	$T_A = 25^\circ C, 10\text{ Hz} \leq f \leq 10\text{ kHz}$		0.003			0.003		%
Ripple Rejection Ratio	$V_{OUT} = -10V, f = 120\text{ Hz}$ $C_{ADJ} = 10\text{ }\mu F$		60 66	77	66	77		dB dB
Long-Term Stability	$T_A = 125^\circ C, 1000\text{ Hours}$		0.3	1		0.3	1	%
Thermal Resistance, Junction to Case	H Package K Package		12 2.3	15 3		12 2.3	15 3	°C/W °C/W

**Note 1:** Unless otherwise specified, these specifications apply  $-55^\circ C \leq T_j \leq +150^\circ C$  for the LM137HV,  $-25^\circ C \leq T_j \leq +150^\circ C$  for the LM237HV,  $0^\circ C \leq T_j \leq +125^\circ C$  for the LM337HV;  $|V_{IN}-V_{OUT}| = 5V$ ; and  $I_{OUT} = 0.1A$  for the TO-39 package and  $I_{OUT} = 0.5A$  for the TO-3 package. Although power dissipation is internally limited, these specifications are applicable for power dissipations of 2W for the TO-39 and 20W for the TO-3.  $I_{MAX}$  is 1.5A for the TO-3 package and 0.2A for the TO-39 package.

**Note 2:** Regulation is measured at constant junction temperature, using pulse testing with a low duty cycle. Changes in output voltage due to heating effects are covered under the specification for thermal regulation. Load regulation is measured on the output pin at a point 1/8" below the base of the TO-3 and TO-39 packages.

**Note 3:** Selected devices with tightened tolerance reference voltage available.


## Schematic Diagram



## Thermal Regulation


When power is dissipated in an IC, a temperature gradient occurs across the IC chip affecting the individual IC circuit components. With an IC regulator, this gradient can be especially severe since power dissipation is large. Thermal regulation is the effect of these temperature gradients on output voltage (in percentage output change) per Watt of power change in a specified time. Thermal regulation error is independent of electrical regulation or temperature coefficient, and occurs within 5 ms to 50 ms after a change in power dissipation. Thermal regulation depends on IC layout as well as electrical design. The thermal regulation of a voltage regulator is defined as the percentage change of  $V_{OUT}$ , per Watt, within the first 10 ms after a step of power is applied. The LM137HV's specification is 0.02%/W, max.

In Figure 1, a typical LM137HV's output drifts only 3 mV (or 0.03% of  $V_{OUT} = -10V$ ) when a 10W pulse is applied for 10 ms. This performance is thus well inside the specification limit of  $0.02\%/\text{W} \times 10\text{W} = 0.2\% \text{ max}$ . When the 10W pulse is ended, the thermal regulation again shows a 3 mV step as the LM137HV chip cools off. Note that the load regulation error of about 8 mV (0.08%) is additional to the thermal regulation error. In Figure 2, when the 10W pulse is applied for 100 ms, the output drifts only slightly beyond the drift in the first 10 ms, and the thermal error stays well within 0.1% (10 mV).



LM137HV,  $V_{OUT} = -10V$   
 $V_{IN}-V_{OUT} = -40V$   
 $I_L = 0A \rightarrow 0.25A \rightarrow 0A$   
Vertical sensitivity, 5 mV/div



FIGURE 1



LM137HV,  $V_{OUT} = -10V$   
 $V_{IN}-V_{OUT} = -40V$   
 $I_L = 0A \rightarrow 0.25A \rightarrow 0A$   
Horizontal sensitivity, 20 ms/div


FIGURE 2

## Connection Diagrams




## Typical Applications (Continued)

### Adjustable High Voltage Regulator




\*The 10  $\mu$ F capacitors are optional to improve ripple rejection


### Current Regulator



### Adjustable Current Regulator




### Negative Regulator with Protection Diodes



\*When C<sub>2</sub> is larger than 20  $\mu$ F, D1 protects the LM137HV in case the input supply is shorted

\*\*When C<sub>2</sub> is larger than 10  $\mu$ F and -V<sub>OUT</sub> is larger than -25V, D2 protects the LM137HV in case the output is shorted

### High Stability -40V Regulator



\*Use resistors with good tracking TC < 25 ppm/°C

## Typical Performance Characteristics (H and K-STEEL Package)

